

- [54] **COMMUNICATION TERMINAL  
EQUIPMENT AND CALL INCOMING  
CONTROL METHOD**
- [75] Inventors: **Hiroshi Yasuda; Morihiko Hayashi,**  
both of Kanagawa; **Michihiro Kaneko,**  
Tokyo; **Michihito Nakagawa,**  
Kanagawa, all of Japan
- [73] Assignee: **Sony Corporation, Tokyo, Japan**
- [21] Appl. No.: **08/571,650**
- [22] Filed: **Dec. 13, 1995**
- [30] **Foreign Application Priority Data**  
Dec. 19, 1994 [JP] Japan ..... 6-335016
- [51] Int. Cl.<sup>6</sup> ..... **H04Q 7/32**
- [52] U.S. Cl. .... **455/567; 455/564; 455/550;**  
**455/403; 379/418; 379/355; 379/373**
- [58] **Field of Search** ..... **455/567, 564,**  
**455/550, 403, 572, 575, 412; 379/418,**  
**355, 373; 340/825.44**
- [56] **References Cited**

#### U.S. PATENT DOCUMENTS

4,504,707	3/1985	Lucchesi .	
4,935,735	6/1990	DeLuca et al. .	
5,233,641	8/1993	Maeda .....	455/567
5,276,729	1/1994	Higuchi et al. ....	455/403
5,329,577	7/1994	Norimatsu .	
5,406,618	4/1995	Knuth et al. ....	455/412
5,442,814	8/1995	Seo .....	455/403

5,491,745	2/1996	Roeder .....	455/564
5,493,285	2/1996	Yoshizawa .....	340/825.44
5,625,683	4/1997	Nazanin et al. ....	379/355
5,651,052	7/1997	Serrano .....	455/567
5,657,372	8/1997	Ahlberg et al. ....	455/403

#### FOREIGN PATENT DOCUMENTS

0275193	7/1988	European Pat. Off. .
0408027	1/1991	European Pat. Off. .
0502617	9/1992	European Pat. Off. .
0772334	5/1997	European Pat. Off. .
0799534A	4/1995	Japan .
9413065	6/1994	WIPO .

*Primary Examiner*—Wellington Chin  
*Assistant Examiner*—Keith Ferguson  
*Attorney, Agent, or Firm*—Jay H. Maioli

#### [57] **ABSTRACT**

In a communication terminal equipment and in a method of controlling call incoming, unnecessary noises in a period from the start of an alert sound to carrying out of the next operation can be reduced. When a predetermined operation is effected under the condition that an alert sound is ringing, the alert sound is stopped or the volume of the alert sound is reduced at least over a duration of call incoming. Thus, such a fear that persons in the surroundings may be troubled by the continuous ringing of the alert sound can be remarkably reduced. Further, since the situation that a power supply is cut off forcibly during call origination can be avoided, the fear that a person on the call origination side may be given an unpleasant feeling can be eliminated.

**19 Claims, 5 Drawing Sheets**